

EL

Standard Connection Accessories

- Junction Box Connection Kits for SRL, SRF and CWM Applications
- Splice & Tee Kits for SRL, SRF and CWM Applications
- End Seal Kits for SRL and SRF Applications



Description

Each model in the EL Series Installation Accessories for Chromalox Rapid Trace Heating Cable products is designed to satisfy the demands of a particular operation. These high-quality models combine a variety of functions in a convenient, easy to use and economical package.

Applications

Connection of selected rapid trace heating cables to customer supplied power wiring in any of the following applications:

- Freeze Protection
- Hydrocarbon and Chemical Product Piping
- Process Temperature Maintenance
- Fluid Flow and Viscosity Maintenance.

Approvals

- UL*** Listed for ordinary areas
- CSA*** Certified for ordinary areas
- FM**** Approved for ordinary areas

* Does not include SSK

** Does not include SSK and PJB

† HSK-PC is CSA certified for ordinary areas only

Ordering Information

Model	Used With
Power Connection Kit	
SSK PJB	SRF-CR, SRL-CR, SRL-CT, CWM-CT, SRP-CT
HSK-PC †	SRF-CR, SRF-CT
Splice & Tee Kit	
RT-RST RT-TST	SRL-CR, SRP-CT
End Seal Kit	
RT-RES	SRL-CR, SRF-CR
To Order — Refer to the DL & EL General Application Accessories in this section.	

EL

Standard Connection Accessories (*cont'd.*)

Accessories



Junction Box Connection Kit SSK (393617)

- (1) compression fitting
- (1) pipe stand off
- (1) tube of RTV sealant
- (1) O-ring
- (1) 1" locknut
- (1) self-regulating cable grommet
- (1) constant wattage cable grommet
- (1) silicone boot
- (2) uninsulated barrel connectors
- (2) insulated barrel connectors



Caution Labels CL-1 (382424)

- (5) electric heat tracing caution labels, weather resistant



Rain Tight Junction Box PJB (393676)

Polycarbonate watertight enclosure for use with SSK



Splice & Tee Kit (for Constant Wattage and SRM/E Cable) RT-TST (383566)

- (5) 7" long large heat shrink tubes
- (10) 1-1/2" long small heat shrink tubes
- (5) 10" lengths of sealant tape
- (15) uninsulated barrel connectors
- (1) tube of RTV sealant



End Seal Kit (for SRL cable) RT-RES (383574)

- (5) 1/2" diameter heat shrink caps



Splice & Tee Kit (for SRL cable) RT-RST (383558)

- (5) 8" long heat shrink tubes
- (5) 1/2" lengths of sealant tape
- (10) insulated barrel connectors
- (5) uninsulated barrel connectors



Conduit Hub w/Grounding Lug CCH-2 (385650)

Corrosion resistant hub for 3/4" conduit. Fits opening in PJB, DL, U Series and DTS. Includes ground connector.



Power Connection & End Seal Kit HSK-PC (387495)

Heat shrink power and end termination kit for SRF heat trace cables. CSA approved for grease waste, frost heave and freeze protection applications.