

Kerotest Insulators

Zunt Monolithic Insulating Joint



Product Brief

The Kerotest Zunt Insulating Joints are manufactured to ISO 9001 standards. The solid weld design is economical and available in a broad size range from 1/2" to 120", ANSI 150 to 2500. There is no assembly required and no maintenance.

Features/Benefits

- **Compact design**
- **Low profile**
- **Complete range of sizes** and pressure classes
- **Joint internally lined** with epoxy resin to effectively prevent bridging of the insulating gap
- **Weld preps per API 5L** (ANSI B16.25 available)
- **All welding processes are in accordance with ASME VIII and IX**
- **Joints are manufactured to applicable ANSI, ASTM, ASME, AISI, API, IEC, and ISO standards**
- **Factory tested** to verify the mechanical integrity and electrical resistance to satisfy cathodic protection requirements
- **Designed and manufactured to ISO 9001 quality standards**
- **Joints are epoxy coated**
- **Eliminate electrical shorts** and stop stray current in pipeline systems
- **Most economical and reliable** cathodic protection for pipeline systems
- **Can be installed above or below ground**
- **Reduced installation time** (just two welds) eliminates field assembly of bulky insulated flanges and bolted couplings
- **Long-term electrical resistance** does not depend on installer assembly of insulation kit
- **Eliminates costly maintenance** to field repair flange leaks and electrical shorts

All product names referenced herein are trademarks of their respective companies.



Kerotest Manufacturing Corp.
5500 Second Avenue • Pittsburgh, PA 15207
412.521.7688 • Fax: 412.521.5990
www.Kerotest.com • Sales@Kerotest.com